

**A step in the right direction**

Designed to be installed in front of a patio door, this heater will provide heat the whole length of the door by creating a screen of warm air to cover the glass surface, inhibiting cold-air infiltration and preventing condensation build-up.

Thanks to its sturdy, 18-gauge steel construction, this heater can actually serve as a step at the door sill. Don't let your patio door become a pain during the winter – install a Stelpro **PDH** heater!



**{features}**

<b>color</b>	white (W) or almond (A)
<b>finish</b>	epoxy-polyester powdercoat
<b>manufacturing</b>	<ul style="list-style-type: none"> <li>· 4 x 4 in. compact profile</li> <li>· heavy-duty, 18-gauge steel cabinet that may be used as a step</li> <li>· thermal protection with automatic reset</li> <li>· full-length wireway</li> </ul>
<b>wattage &amp; voltage</b>	see the selection table
<b>element</b>	<ul style="list-style-type: none"> <li>· single tubular, stainless steel sheathed element with boxed aluminum fins for improved heat dissipation</li> <li>· securely fastened at its center, floating in nylon sleeves at each end, eliminating expansion and contraction noises</li> </ul>
<b>control</b>	<ul style="list-style-type: none"> <li>· built-in thermostat accessible without removing front grille - optional (not included)</li> <li>· low voltage relay kit - optional (not included)</li> </ul>
<b>installation</b>	<ul style="list-style-type: none"> <li>· surface mount</li> <li>· wall or floor mounted with pedestal kit - optional (not included)</li> <li>· blank sections and fillers available for a continuous effect - optional (not included)</li> </ul>
<b>warranty</b>	<ul style="list-style-type: none"> <li>· 10 years (element)</li> <li>· 1 year (unit)</li> </ul>

**{accessories}**

code	description
<b>PDHT12*</b>	built-in tamper-proof single pole thermostat
<b>PDHT22*</b>	built-in tamper-proof double pole thermostat
<b>PDHRE153*</b>	built-in electronic low voltage relay [15 A @ 120, 208, 277 or 347 V]
<b>PDHRE156*</b>	built-in electronic low voltage relay [6 A @ 600 V]
<b>PDHRE153T*</b>	built-in electronic low voltage relay c/w transformer 24 V [15 A @ 208, 277 or 347 V]
<b>PK2*</b>	pedestal kit (kit of two)
<b>PDHJS*</b>	joiner strip (2 in.)
<b>PDHC90*</b>	inside corner (back measures 7 7/8 in. long on each side)
<b>PDHOC90*</b>	outside corner (back measures 7 7/8 in. long on each side)
<b>PDHCB**</b>	clean back (fully finished, no mounting holes or knockouts)

electronic relays can receive a pulsed or on/off signal

\* add **W** for white or **A** for almond

\* factory installed

\* factory installation is strongly recommended



**compact & solid**  
4 x 4 inches

**pages 90 to 96**  
wall thermostats & accessories

**{selection table}**

product code	power watts	voltage volts	width		weight	
			mm	in.	kg	lb
PDH0502	500/375	240/208	851	33 1/2	5.9	13
PDH0508	500	208	851	33 1/2	5.9	13
PDH0507	500	277	851	33 1/2	5.9	13
PDH0503	500	347	851	33 1/2	5.9	13
---	500	480	851	33 1/2	5.9	13
---	500	600	851	33 1/2	5.9	13
PDH0752	750/560	240/208	1219	48	7.7	17
PDH0758	750	208	1219	48	7.7	17
PDH0757	750	277	1219	48	7.7	17
PDH0753	750	347	1219	48	7.7	17
PDH0755	750	480	1219	48	7.7	17
PDH0756	750	600	1219	48	7.7	17
PDH1002	1000/750	240/208	1524	60	9.0	20
PDH1008	1000	208	1524	60	9.0	20
PDH1007	1000	277	1524	60	9.0	20
PDH1003	1000	347	1524	60	9.0	20
PDH1005	1000	480	1524	60	9.0	20
PDH1006	1000	600	1524	60	9.0	20
PDH1252	1250/940	240/208	1829	72	11.0	25
PDH1258	1250	208	1829	72	11.0	25
PDH1257	1250	277	1829	72	11.0	25
PDH1253	1250	347	1829	72	11.0	25
PDH1255	1250	480	1829	72	11.0	25
PDH1256	1250	600	1829	72	11.0	25
PDH1502	1500/1125	240/208	2204	86 7/8	14.1	31
PDH1508	1500	208	2204	86 7/8	14.1	31
PDH1507	1500	277	2204	86 7/8	14.1	31
PDH1503	1500	347	2204	86 7/8	14.1	31
PDH1505	1500	480	2204	86 7/8	14.1	31
PDH1506	1500	600	2204	86 7/8	14.1	31
PDH1752	1750/1315	240/208	2542	100 1/16	17.3	38
PDH1758	1750	208	2542	100 1/16	17.3	38
PDH1757	1750	277	2542	100 1/16	17.3	38
PDH1753	1750	347	2542	100 1/16	17.3	38
PDH1755	1750	480	2542	100 1/16	17.3	38
PDH1756	1750	600	2542	100 1/16	17.3	38
PDH2002	2000/1500	240/208	2879	113 3/8	18.6	41
PDH2008	2000	208	2879	113 3/8	18.6	41
PDH2007	2000	277	2879	113 3/8	18.6	41
PDH2003	2000	347	2879	113 3/8	18.6	41
PDH2005	2000	480	2879	113 3/8	18.6	41
PDH2006	2000	600	2879	113 3/8	18.6	41

add **W** for white or **A** for almond.  
 --- not available

**PDH**

**{technical drawing}**

