

{universal thermostat guard}



TG511A1000



key (included)
the ambient temperature
can be changed only by the
key owner

{features}

manufacturing	clear plastic
dimensions	6 1/16 x 5 1/16 x 2 5/8 in.
control	<ul style="list-style-type: none"> fit with the majority of the electronic thermostats features a tumbler lock (keys included) can be installed without removing the thermostat from the wall protection against vandalism, damage and unauthorized tampering of settings

{selection table}

code	description
TG511A1000	universal thermostat guard

{thermostat guard}



F290143



key (included)
the ambient temperature
can be changed only by the
key owner

{features}

manufacturing	clear plastic
control	<ul style="list-style-type: none"> fit with the majority of the electronic thermostats features a tumbler lock (keys included) protection against vandalism, damage and unauthorized tampering of settings

{selection table}

code	description
F290143	thermostat guard

{mechanical timer}



FD60M



installation
simple et rapide sur
une plaque murale (non
comprise)

{features}

color	white
contrôle	60-minute timer
installation	decora wall plate (not included)


{selection table}

code	description
FD60MCW70	60-minute timer

{electronic low voltage relay}



RE253T



RE253C



RE306C



{features}

manufacturing	<ul style="list-style-type: none"> electronic low voltage
wattage & voltage	see the selection table
control	<ul style="list-style-type: none"> triac or on/off c/w transformer (RE253T)

{selection table}

code	description
RE253C	electronic low voltage relay [25 A @ 208, 277 ou 347 V]
RE253T	electronic low voltage relay [25 A @ 208, 277 ou 347 V]
RE306C	electronic low voltage relay [30 A @ 600 V]

{smaller-sized electronic low voltage relays}



RE153T



RE156



RE153




{features}

manufacturing	<ul style="list-style-type: none"> electronic low voltage
wattage & voltage	see the selection table
control	<ul style="list-style-type: none"> triac or on/off c/w transformer (RE153T)

{selection table}

code	description
RE153	electronic low voltage relay [15 A @ 120, 208, 277 ou 347 V]
RE156	electronic low voltage relay [6 A @ 600 V]
RE153T	electronic low voltage relay [15 A @ 208, 277 ou 347 V]

{electric relay}



R841C1011



{features}

manufacturing	<ul style="list-style-type: none"> electric c/w transformer 24 V (with the exception of R841D1028)
wattage & voltage	see the selection table

{selection table}

code	description
R841C1011	electric relay c/w transformer 24 V [5000 W @ 208 V]
R841C1169	electric relay c/w transformer 24 V [6000 W @ 240 V]
R841C1144	electric relay c/w transformer 24 V [6000 W @ 347 V]
R841C1151	electric relay c/w transformer 24 V [6000 W @ 600 V]
R841D1036	electric relay w/o transformer 24 V