

# ELN | EL-NIÑO™

## HAND DRYER



## THE PERFECT COMBINATION OF POWER AND STYLE

The El-Niño is absolutely incredible; you have to try it to believe it. This powerful hand dryer dries hands completely in only ten seconds. The El-Niño is a quiet, energy-efficient solution that combines quick drying with overall savings. This state-of-the-art hand dryer offers four personalized operating modes to meet your needs. Save time and money with the stylish El-Niño!

- **NOISE LEVEL AND HEAT CONTROL**  
FOUR PERSONALIZED MODES
- **ENERGY EFFICIENT IN ECONOMICAL AND HARMONY MODES**
- **HEAVY-DUTY DIE-CAST ALUMINUM ALLOY SHELL**
- **STYLISH AND COMPACT**
- **SEMI-RECESSED INSTALLATION**  
LESS THAN 4 INCHES

### COLOURS

- **standard:** white
- **luxury finish:** brushed chrome (surcharge)
- **Orora (optional):** refer to [www.stelpro.com/en-CA/Orora](http://www.stelpro.com/en-CA/Orora)

### FINISH

- epoxy-polyester powdercoat or chrome-plated

### MANUFACTURING

- rib reinforced shell, solidly constructed of die-cast aluminum alloy
- lightweight, heavy duty and rustproof shell
- wall bracket with two chrome-plated tamper-proof bolts

### ELEMENT

- nichrome element located in motor section

### CONTROL

- four personalized operating modes to meet your needs
- infrared optical sensor located next to the air outlet activates and deactivates the hand dryer
- 60-second lockout feature is activated if hands are not removed before this time

### INSTALLATION

- surface mounted
- optional semi-recessed installation with depth of 4 inches or less; meets ADA standards (Americans with Disabilities Act)

### WARRANTY

- five years,\*three years on electronic components



Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at [www.stelpro.com](http://www.stelpro.com).



FC\_ELN\_EN\_010623

## TECHNICAL SPECIFICATIONS

PRODUCT	POWER (WATTS)*			VOLTAGE	AMPERAGE	WEIGHT		PRICE	
CODE	ELEMENT	MOTOR	TOTAL	VOLTS	AMPERES	KG	LB	W	BC
<b>ELNV0901A</b>	900	550	1450	120	10	4.4	9.8	<b>1 050.00</b>	<b>1 226.00</b>
<b>ELNV0902A</b>	900	550	1450	240	5.8	4.4	9.8	<b>1 050.00</b>	<b>1 226.00</b>
<b>ELNV0908A</b>	900	550	1450	208	5	4.4	9.8	<b>1 050.00</b>	<b>1 227.00</b>

Add W for white or BC for brushed chrome (consult the optional colours chart or contact your Stelpro representative for all other colours).

\*Data obtained in Normal/High mode

## ACCESSORIES

PRODUCT	DESCRIPTION	PRICE
<b>ELNKOE</b>	Pre-drilled sleeve for electrical connection	<b>55.00</b>
<b>SHDXL-89W</b>	Wall guard - white (15 3/4 in. x 31 3/4 in. x 1/16 in. – 40 cm x 81 cm x 0.16 cm) – set of two	<b>342.00</b>
<b>SHDXL-89B</b>	Wall guard - black (15 3/4 in. x 31 3/4 in. x 1/16 in. – 40 cm x 81 cm x 0.16 cm) – set of two	<b>342.00</b>
<b>SHDXL-89S</b>	Wall guard - stainless steel (15 3/4 in. x 31 3/4 in. x 1/16 in. – 40 cm x 81 cm x 0.16 cm) – set of two	<b>543.00</b>

### PRE-DRILLED SLEEVE FOR ELECTRICAL CONNECTION

The pre-drilled sleeve allows for an electrical connection to the top of the unit in the case when access to the junction box from inside the wall or the bottom of the unit is problematic or not required (only available for surface mounted installation).



### WALL GUARD

The wall guard protects the wall under the hand dryer from drops of water due to wet hands being blown dry and makes cleaning easier.



## OPERATING MODES


The El-Niño's built-in electronic control lets you personalize your unit to meet all your needs.

MODE	ENERGY SAVINGS	AIR SPEED OR AIR FLOW	HEATING POWER	NOISE LEVEL	DRYING TIME
<b>ULTIMATE – Normal/High mode</b> High air speed and full heating power for quick drying Ideal for: stadiums, arenas, theatres, public places and warehouses	---				
<b>COMFORT – Normal/Low mode</b> Reduced air speed and moderate heating power for comfortable noise level and heat range Ideal for: libraries, small restaurants and coffee shops	---				
<b>ECONOMICAL – Eco/High mode</b> High air speed without heat for quick drying with energy and cost savings Ideal for: schools, universities, amusement parks, warehouses and large restaurants			---		
<b>HARMONY – Eco/Low mode</b> Reduced air speed without heat for energy savings and a moderate noise level Ideal for: hospitals, libraries, daycares, small restaurants and coffee shops			---		

MODE	AIR SPEED (LFM)		TOTAL POWER	NOISE LEVEL (DB)	
	AT AIR OUTLET	AT HAND LEVEL*	WATTS	WITHOUT HANDS	WITH HANDS
<b>ULTIMATE</b>	19 000	16 000	1450	77	90
<b>COMFORT</b>	11 400	9600	1175	72	85
<b>ECONOMICAL</b>	19 000	16 000	550	77	90
<b>HARMONY</b>	11 400	9600	465	72	85

\*4 inches below

# TECHNICAL DRAWINGS



## RECOMMENDED INSTALLATION HEIGHTS

Distance between floor and bottom of hand dryer

MEN	WOMEN	TEENAGERS	CHILDREN	HANDICAPPED
45 in. (115 cm)	43 in. (110 cm)	41 in. (105 cm)	35 in. (90 cm)	37 in. (95 cm)

### 3 LEVELS OF DETECTION

Adjust the sensitivity level of your hand dryer to meet usage requirements.

Detection distances may vary depending on lighting conditions.



**MAXIMAL DETECTION – STANDARD (APPROX. 4 IN. – 10 CM)**

**MEDIUM DETECTION – DECREASED (APPROX. 3 IN. – 7.6 CM)**

**MINIMAL DETECTION – MINIMUM (APPROX. 2 IN. – 5 CM)**

