## MIR | MIRAGE™ CONVECTOR





# **MIRAGE**™

## THE MOST DISCREET ON THE MARKET!

The Mirage convector has a unique, modern and discreet look and offers unquestionable efficiency. Available with or without an ultraprecise integrated electronic thermostat and in several voltages, the Mirage is suitable for rooms in homes or businesses. With its simple facade and elegant design, the Mirage blends in with any decor.

- BLENDS IN WITH ANY DECOR
- STURDY ONE-PIECE FRONT PANEL
- TOTALLY QUIET
- BUILT-IN ELECTRONIC THERMOSTAT (OPTIONAL)
   WITH BACKLIT SCREEN
- ADAPTS TO MULTIPLE MARKETS AVAILABLE IN 120 V, 208 V, 240 V, 347 V AND 600 V

#### **COLOURS**

- standard: white, soft white
- Orora (optional): refer to www.stelpro.com/en-CA/Orora

#### **FINISH**

• epoxy-polyester powdercoat

#### **MANUFACTURING**

- 20-gauge steel cabinet and front
- the cabinet height improves the chimney effect
- bottom air intake and top air discharge
- 6 ft (2 m) 16 gage molded cable with 3-prong grounded, 120 V plug (MIR1501P model)

#### **ELEMENTS**

 two stainless steel tubular sheathed elements insulated with nylon sleeves reducing expansion and contraction noises

#### **CONTROL**

- electronic thermostat required: built-in electronic thermostat with LCD screen (optional) or electronic wall thermostat (not included)
- automatic temperature lowering at night (Automatic mode)
- maximum temperature setpoint lock option (Security mode)

#### **INSTALLATION**

- · surface mounted only
- · wall mounted at least 4 in. from the floor
- concealed mounting bracket (included)
- back entry plate with cable clamps (included)

#### WARRANTY

five years, \*three years on electronic components



**BUILT-IN ELECTRONIC THERMOSTAT AVAILABLE** FOR THE 120 V TO 240 V MODELS



#### **IDEAL FOR:**

kitchen, living room, bedroom, basement, commercial space, office



TECHNICAL SPECIFICATIONS												
BUILT-IN THERMOSTAT		WITHOUT THERMOSTAT		POWER	VOLTAGE	HEIGHT		LENGTH		WEIGHT		
CODE	PRICE	CODE	PRICE	WATTS	VOLTS	MM	IN.	MM	IN.	KG	LB	
MIR0501	349.00	MIR0501WC	280.00	500	120	457	18	444	17 1/2	5.3	11.75	
MIR0508	347.00	MIR0508WC	280.00	500	208	457	18	444	17 1/2	5.3	11.75	
MIR0502	302.00	MIR0502WC	237.00	500/375	240/208	457	18	444	17 1/2	5.3	11.75	
		MIR0503WC	353.00	500	347	457	18	444	17 1/2	5.3	11.75	
MIR1001	368.00	MIR1001WC	297.00	1000	120	457	18	597	23 1/2	6.7	14.75	
MIR1008	368.00	MIR1008WC	298.00	1000	208	457	18	597	23 1/2	6.7	14.75	
MIR1002	323.00	MIR1002WC	254.00	1000/750	240/208	457	18	597	23 1/2	6.7	14.75	
		MIR1003WC	370.00	1000	347	457	18	597	23 1/2	6.7	14.75	
		MIR1006WC	370.00	1000	600	457	18	597	23 1/2	6.7	14.75	
MIR1501	382.00	MIR1501WC	312.00	1500	120	457	18	749	29 1/2	8	17.75	
MIR1508	384.00	MIR1508WC	314.00	1500	208	457	18	749	29 1/2	8	17.75	
MIR1502	338.00	MIR1502WC	270.00	1500/1125	240/208	457	18	749	29 1/2	8	17.75	
		MIR1503WC	386.00	1500	347	457	18	749	29 1/2	8	17.75	
		MIR1506WC	386.00	1500	600	457	18	749	29 1/2	8	17.75	
MIR2008	401.00	MIR2008WC	329.00	2000	208	457	18	902	35 1/2	9.4	20.75	
MIR2002	355.00	MIR2002WC	283.00	2000/1500	240/208	457	18	902	35 1/2	9.4	20.75	
		MIR2003WC	403.00	2000	347	457	18	902	35 1/2	9.4	20.75	
		MIR2006WC	403.00	2000	600	457	18	902	35 1/2	9.4	20.75	
MODEL WITH 120 V PLUG (RESIDENTIAL OUTLET)												
MIR1501P*	407.00			1500	120	457	18	749	29 1/2	8	17.75	

Add W for white or SW for soft white (or consult the optional colour chart and contact your Stelpro representative for all other colours).

Mechanical wall thermostats are not compatible with the without thermostat model (WC). An electronic thermostat is required. Models also available in 277 V and 480 V.

\* Available in white only
--- not available

	ACCESSORIES	
PRODUCT	DESCRIPTION	PRICE
MIRRE153*	built-in electronic low voltage relay [15 A @ 120 V-347 V]	80.00
MIRRE156*	built-in electronic low voltage relay [6 A @ 600 V]	140.00
MIRRE153T*	built-in electronic low voltage relay c/w transformer 24 V [15 A @ 208 V-347 V]	100.00

Electronic relays can receive a PWM (pulsed width modulation) or digital (on/off) signal.

\* Factory installed

### **TECHNICAL DRAWINGS**

