

AMIR | MIRAGE™

CONVECTOR



MIRAGE™

THE MOST DISCREET ON THE MARKET!

The Mirage convector has a unique, modern and discreet look and offers unquestionable efficiency. Available with or without an ultra-precise integrated electronic thermostat and in several voltages, the Mirage is suitable for rooms in homes or businesses. With its simple facade and elegant design, the Mirage blends in with any decor.

- **BLENDS IN WITH ANY DECOR**
- **STURDY ONE-PIECE FRONT PANEL**
- **TOTALLY QUIET**
- **BUILT-IN ELECTRONIC THERMOSTAT (OPTIONAL)**
WITH BACKLIT SCREEN
- **ADAPTS TO MULTIPLE MARKETS**
AVAILABLE IN 120 V, 208 V,
240 V, 277 V AND 480 V



BUILT-IN ELECTRONIC THERMOSTAT AVAILABLE
FOR THE 120 V TO 240 V MODELS



ALSO AVAILABLE

EASY INSTALLATION
WITH 120 V PLUG

IDEAL FOR:

kitchen, living room, bedroom, basement, commercial
space, office

COLORS

- **standard:** white, soft white
- **Orora (optional):** refer to www.stelpro.com/en-US/Orora

FINISH

- epoxy-polyester powdercoat

MANUFACTURING

- 20-gauge steel cabinet and front
- the cabinet height improves the chimney effect
- bottom air intake and top air discharge
- 6 ft (2 m) 16 gage molded cable with 3-prong grounded, 120 V plug (AMIR1501P model)

ELEMENTS

- two stainless steel tubular sheathed elements insulated with nylon sleeves reducing expansion and contraction noises

CONTROL

- electronic thermostat required: built-in electronic thermostat with LCD screen (optional) or electronic wall thermostat (not included)
- automatic temperature lowering at night (Automatic mode)
- maximum temperature setpoint lock option (Security mode)

INSTALLATION

- surface mounted only
- wall mounted at least 4 in. from the floor
- concealed mounting bracket (included)
- back entry plate with cable clamps (included)

WARRANTY

- five years, *three years on electronic components

°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-color products. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_MIR_US_200623

TECHNICAL SPECIFICATIONS

BUILT-IN THERMOSTAT	WITHOUT THERMOSTAT	POWER		VOLTAGE	HEIGHT	LENGTH	WEIGHT
CODE	CODE	WATTS	BTU/H	VOLTS	IN.	IN.	LB
AMIR0501	AMIR0501WC	500	2048	120	18	17 1/2	11.75
AMIR0508	AMIR0508WC	500	2048	208	18	17 1/2	11.75
AMIR0502	AMIR0502WC	500/375	2048	240/208	18	17 1/2	11.75
---	AMIR0507WC	500	2048	277	18	17 1/2	11.75
AMIR1001	AMIR1001WC	1000	3413	120	18	23 1/2	14.75
AMIR1008	AMIR1008WC	1000	3413	208	18	23 1/2	14.75
AMIR1002	AMIR1002WC	1000/750	3413	240/208	18	23 1/2	14.75
---	AMIR1007WC	1000	3413	277	18	23 1/2	14.75
---	AMIR1005WC	1000	3413	480	18	23 1/2	14.75
AMIR1501	AMIR1501WC	1500	5119	120	18	29 1/2	17.75
AMIR1508	AMIR1508WC	1500	5119	208	18	29 1/2	17.75
AMIR1502	AMIR1502WC	1500/1125	5119	240/208	18	29 1/2	17.75
---	AMIR1507WC	1500	5119	277	18	29 1/2	17.75
---	AMIR1505WC	1500	5119	480	18	29 1/2	17.75
AMIR2008	AMIR2008WC	2000	6825	208	18	35 1/2	20.75
AMIR2002	AMIR2002WC	2000/1500	6825	240/208	18	35 1/2	20.75
---	AMIR2007WC	2000	6825	277	18	35 1/2	20.75
---	AMIR2005WC	2000	6825	480	18	35 1/2	20.75
MODEL WITH 120 V PLUG (RESIDENTIAL OUTLET)							
AMIR1501P*	---	1500	5119	120	18	29 1/2	17.75

Add W for white or SW for soft white (or consult the optional color chart and contact your Stelpro representative for all other colors).

Mechanical wall thermostats are not compatible with the without thermostat model (WC) – electronic thermostat is required.

* Available in white only --- not available

ACCESSORIES

PRODUCT	DESCRIPTION
MIRRE153*	built-in electronic low voltage relay [15 A @ 120 V-347 V]
MIRRE156*	built-in electronic low voltage relay [6 A @ 600 V]
MIRRE153T*	built-in electronic low voltage relay c/w transformer 24 V [15 A @ 208 V-347 V]

Electronic relays can receive a PWM (pulsed width modulation) or digital (on/off) signal.

* Factory installed

TECHNICAL DRAWINGS

