



RE25 – RE30

ELECTRONIC RELAY – LOW VOLTAGE



RE253C



RE253T



RE306C



These larger models must be installed in an external junction box. A variety of models are available depending on your needs.

- **WITH TRANSFORMER (RE253T)**
- **COMPATIBLE WITH STE241, T822K1018U AND T87K1007U THERMOSTATS**
- **3 TO 32 VDC PULSE OR ALL OR NOTHING (ON/OFF) SIGNAL**
- **EASY TO INSTALL IN A 4" X 4" ELECTRICAL JUNCTION BOX**
- **FROM 120 V TO 600 V**

CONTROL

- pulsed signal (PWM) or all or nothing (on/off) at 24 Vac, 3-32 Vdc signal
- with a transformer (RE253T)
- compatible with the STE241, T822K1018U and T87K1007U thermostats
- two additional relays without transformers can be added to the same control circuit as a relay with a transformer
- installing more than four relays without transformers to the same thermostat is not recommended

INSTALLATION

- the relay must be installed in an external junction box

WARRANTY

- three years

TECHNICAL SPECIFICATIONS

PRODUCT	DESCRIPTION
RE253C	electronic low voltage relay [25 A @ 120 V, 208 V, 240 V, 277 V or 347 V]
RE253T	electronic low voltage relay [25 A @ 208 V, 240 V, 277 V or 347 V] (w/transformer)
RE306C	electronic low voltage relay [30 A @ 120 V-600 V]

DIMENSIONS: RE253: 4.10 in. x 4.10 in. x 2.10 in. (104.1 mm x 104.1 mm x 53.3 mm)
RE306C: 4.76 in. x 4.70 in. x 3 in. (120.9 mm x 119.4 mm x 76.2 mm)