

SCPT

CONSTANT WATTAGE PIPE FREEZE PROTECTION HEATING CABLE



SAY GOODBYE TO FROZEN PIPES

This preassembled heating cable is designed to prevent pipes from freezing and avoid water damage. The cable is easy to install thanks to its 120 V plug, and the integrated thermostat triggers heat only when necessary. The cable is installed on pipes under insulation and protects against freezing down to -40 °C (-40 °F). Ideal for metal or plastic pipes up to 1.5 in. (3.81 cm) in diameter.*

PREVENTS PIPE BREAKAGE AND WATER DAMAGE

IDEAL FOR PLASTIC OR METAL PIPES

LIGHTED PLUG POWER INDICATOR

INTEGRATED THERMOSTAT THAT TRIGGERS AT 3 °C (37 °F) TO PREVENT FREEZING

MANUFACTURING

- tough XLPE inner insulation
- AL foil and continuous ground braid
- weather resistant PVC (high-low temperature) out jacket
- twin conductor
- bending radius of 1 inch
- 2 ft cold lead with plug

WATTAGE

- 7 W/ft

CONTROL

- built-in thermostat

INSTALLATION

- install at a temperature above -10 °C (14 °F)

WARRANTY

- two years

*The cable must never cross over itself. Plastic pipes must always be filled with water.



QUICK PLUG-IN INTO RESIDENTIAL 120 V OUTLET

IDEAL FOR:

pipes at risk of freezing

°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at www.stelpro.com.



TECHNICAL SPECIFICATIONS

PRODUCT	LENGTH	POWER	AMPERAGE	PRICE
CODE	FT	WATTS	AMPS	
120 VOLTS				
SCPT1W0021L0003	3	21	0.2	37.00
SCPT1W0042L0006	6	42	0.4	41.00
SCPT1W0063L0009	9	63	0.5	43.00
SCPT1W0084L0012	12	84	0.7	47.00
SCPT1W0105L0015	15	105	0.9	55.00
SCPT1W0126L0018	18	126	1.1	61.00
SCPT1W0168L0024	24	168	1.4	69.00
SCPT1W0210L0030	30	210	1.8	77.00
SCPT1W0280L0040	40	280	2.3	99.00
SCPT1W0420L0060	60	420	3.5	122.00

