

# SCPT

## CONSTANT WATTAGE PIPE FREEZE PROTECTION HEATING CABLE



### SAY GOODBYE TO FROZEN PIPES

This preassembled heating cable is designed to prevent pipes from freezing and avoid water damage. The cable is easy to install thanks to its 120 V plug, and the integrated thermostat triggers heat only when necessary. The cable is installed on pipes under insulation and protects against freezing down to -40 °F. Ideal for metal or plastic pipes up to 1.5 in. in diameter.\*

#### PREVENTS PIPE BREAKAGE AND WATER DAMAGE

#### IDEAL FOR PLASTIC OR METAL PIPES

#### LIGHTED PLUG POWER INDICATOR

#### INTEGRATED THERMOSTAT THAT TRIGGERS AT 37 °F TO PREVENT FREEZING

#### MANUFACTURING

- tough XLPE inner insulation
- AL foil and continuous ground braid
- weather resistant PVC (high-low temperature) out jacket
- twin conductor
- bending radius of 1 inch
- 2 ft cold lead with plug

#### WATTAGE

- 7 W/ft

#### CONTROL

- built-in thermostat

#### INSTALLATION

- install at a temperature above 14 °F

#### WARRANTY

- two years

\*The cable must never cross over itself. Plastic pipes must always be filled with water.



QUICK PLUG-IN INTO RESIDENTIAL 120 V OUTLET

#### IDEAL FOR:

pipes at risk of freezing

# °STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-color products. For all the latest models and prices, please refer to our website at [www.stelpro.com](http://www.stelpro.com).



FC\_SCPT\_US\_190822

# TECHNICAL SPECIFICATIONS

PRODUCT	LENGTH	POWER	AMPERAGE
CODE	FT	WATTS	AMPS
120 VOLTS			
SCPT1W0021L0003	3	21	0.2
SCPT1W0042L0006	6	42	0.4
SCPT1W0063L0009	9	63	0.5
SCPT1W0084L0012	12	84	0.7
SCPT1W0105L0015	15	105	0.9
SCPT1W0126L0018	18	126	1.1
SCPT1W0168L0024	24	168	1.4
SCPT1W0210L0030	30	210	1.8
SCPT1W0280L0040	40	280	2.3
SCPT1W0420L0060	60	420	3.5

