

# ASMT402AD | MAESTRO™

SMART THERMOSTAT

4000 W



## MAESTRO™



## ORCHESTRATING COMFORT

Use the Maestro thermostat with the Maestro controller•thermostat to turn your house into a smart home in a snap! Indeed, the Maestro thermostat reveals its full potential when it's paired with the Maestro controller•thermostat. It can also be linked to an existing Zigbee network controlled by any Zigbee-compatible controller. Maestro is the smart home comfort solution!



**COMPATIBLE WITH MAESTRO CONTROLLER OR ZIGBEE HUB**  
CONTROL AT YOUR FINGERTIPS WITH YOUR SMARTPHONE OR MOBILE DEVICE



**RELATIVE ROOM HUMIDITY DISPLAY**



**ENERGY CONSUMPTION REPORTS†**  
FOR OPTIMAL ENERGY EFFICIENCY



**ELECTRICITY SAVINGS**  
ENERGY SAVINGS UP TO 25%  
DEPENDING ON USE\*

### COMPATIBILITY

- Maestro controller•thermostat or Zigbee hub required
- Zigbee 3.0

### COLOR

- white

### FINISH

- molded plastic

### WATTAGE AND VOLTAGE

- 150 W to 2000 W @ 120 V
- 260 W to 3400 W @ 208 V
- 300 W to 4000 W @ 240 V

### CONTROL

- Maestro environment options include:
  - outdoor temperature or relative room humidity display
  - energy consumption reports

- lock screen capability
- screen backlighting
- radical temperature decrease detection (open-window feature)
- motion-activated screen
- Zigbee home automation environment compatibility

### ACCURACY

- accurate ambient temperature control of ± 1 °F
- CSA C828-13
- temperature sensing with thermistor

### TEMPERATURE RANGE

- 41 to 86 °F

### WARRANTY

- three years

† with Maestro ecosystem  
\* study carried out by an independent university team

## ACCESSORIES

PRODUCT	DESCRIPTION
SMAMPLIZB	Zigbee signal amplifier
SMREPETZB	Zigbee signal repeater

COMPATIBLE WITH



FOR HOME AUTOMATED SYSTEM COMPATIBILITIES AND INSTRUCTIONS ON CONNECTING TO YOUR MAESTRO THERMOSTAT, VISIT [WWW.STELPRO.COM/MAESTRO](http://WWW.STELPRO.COM/MAESTRO).

## TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	COLOR	PACKAGING
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ		
ASMT402AD	150/260/300	2000/3400/4000	120/208/240	16.7	60	WHITE	BOX

Dimensions: 5 3/8 in. wide, 5 3/8 in. high and 1 1/4 in. deep

# STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-color products. For all the latest models and prices, please refer to our website at [www.stelpro.com](http://www.stelpro.com).



FC\_SMT402AD\_US\_220421