## ST302P-ST402P

### ELECTRONIC THERMOSTATS FOR BASEBOARDS AND CONVECTORS

#### **PROGRAMMABLE**



3000 W









# **\$\$\$\$\$**

## CUSTOMIZED COMFORT IN THREE EASY STEPS

Harmonious design, superior technology and safe operation merge in Stelpro's all-new programmable electronic thermostats for baseboards and convectors. With simple three-step programming, you can manage your home's comfort while enjoying energy savings up to 20% compared to a mechanical thermostat and up to 8%\* compared to a non-programmable thermostat.

- ENERGY SAVINGS UP TO 20%\*
- SIMPLE THREE-STEP PROGRAMMING
- UNBEATABLE ACCURACY
  QUALITY SENSORS AND ADVANCED
  ALGORITHMS
- **SAFE DESIGN**SEALED HOUSING
- S³ MOUNTING PLATE STURDY, SIMPLE AND SAFE INSTALLATION

#### **COLOUR**

white

#### **FINISH**

· molded plastic

#### WATTAGE AND VOLTAGE

#### ST302P

- 150 W to 1500 W @ 120 V
- 260 W to 2600 W @ 208 V
- 300 W to 3000 W @ 240 V

#### ST402P

- 150 W to 2000 W @ 120 V
- 260 W to 3475 W @ 208 V
- 300 W to 4000 W @ 240 V

#### **CONTROL**

- two-wire connection
- possibility of four events on weekdays and two events on weekends
- protection against power failure (two hours)
- · display in Celsius or Fahrenheit

#### **ACCURACY**

- accurate ambient temperature control of ± 0.5 °C (1°F)
- CSA C828-19
- · temperature sensing with thermistor

#### TEMPERATURE RANGE

• 5 to 30 °C (41 to 86 °F)

#### WARRANTY

- · five years
- \* independent study

		TECHNIC	AL SPECIF	ICATIONS		
PRODUCT	WATTS		VOLTAGE	MAX. AMPERAGE	FREQUENCY	PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ	
ST302P	150/260/300	1500/2600/3000	120/208/240	12.5	60	57.00
ST402P	150/260/300	2000/3475/4000	120/208/240	16.7	60	60.00

 $\hbox{DIMENSIONS ST302P: 4,35 in. (110,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep DIMENSIONS ST402P: 4,94 in. (125,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep DIMENSIONS ST402P: 4,94 in. (125,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep DIMENSIONS ST402P: 4,94 in. (125,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep DIMENSIONS ST402P: 4,94 in. (125,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep DIMENSIONS ST402P: 4,94 in. (125,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep DIMENSIONS ST402P: 4,94 in. (125,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep DIMENSIONS ST402P: 4,94 in. (125,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep DIMENSIONS ST402P: 4,94 in. (125,5 mm) wide, 4,94 in. (125,5 mm) high and 1,38 in. (35 mm) deep DIMENSIONS ST402P: 4,94 in. (125,5 mm) wide, 4,94 in. (125,$ 





