

# TH140-28-01-B

ELECTRONIC THERMOSTAT – LINE AND LOW VOLTAGE – 7-DAY PROGRAMMABLE



This versatile thermostat can control very low voltage systems up to 240 V.

- **TWO-WIRE THERMOSTAT (R, W)**
- **COMPATIBLE WITH ALL RE, RM AND R841 RELAYS**
- **TEMPERATURE IN DEGREES CELSIUS AND FAHRENHEIT**
- **7-DAYS PROGRAMMABLE**

## COLOUR

- white

## FINISH

- molded plastic

## VOLTAGE

- Max: 5 A @ 24 V – 240 V resistive
- Max: 2 A @ 24 V – 240 V inductive

## CONTROL

- versatile thermostat that controls systems from millivolts to 240 V and is also well-suited for hot water heating
- battery powered (2 AA alkaline batteries)
- terminals R, W (X, C optional remote input)
- temperature sensing with thermistor

## TEMPERATURE RANGE

- 5 to 30°C (40 to 85°F)

## WARRANTY

- one year

## TECHNICAL SPECIFICATIONS

PRODUCT	DESCRIPTION	PRICE
TH140-28-01-B	Electronic prog. thermostat, millivolt to 240V, 5A RES. 2A IND.	111.00

DIMENSIONS: 3 13/16 in. (97 mm) wide, 5 in. (127 mm) high and 1 in. (26 mm) deep

°**STELPRO**

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at [www.stelpro.com](http://www.stelpro.com).