

SSC/SSCM

SNOW MELTING SYSTEM



EXPERIENCE WINTER IN A WHOLE NEW WAY!

Have you ever wished snow could melt from exterior surfaces all on its own? With Stelpro's brand-new snow melting system, your wish is granted! Perfect for residential and commercial outdoor locations, it reduces snow and ice build-up on the ground. Available as a carpet or as a cable for driveways, walkways, sidewalks or stairs, it can be installed under concrete, asphalt and pavers. This year, experience winter a whole new way with Stelpro's snow melting system.

MAT AND CABLE MODELS AVAILABLE

LONGER INFRASTRUCTURE LIFESPAN

GUARDS AGAINST DAMAGE DUE TO ABRASIVES, CHEMICALS AND SNOW REMOVAL EQUIPMENT

CLEARER PATHS AND DRIVEWAY

PREVENTS FALLS AND ACCIDENTS

LESS HOUSEHOLD MAINTENANCE INDOORS

REDUCES THE NEED FOR CHEMICALS AND ABRASIVES

MANUFACTURING

- fluoropolymer-insulated double heating element
- PVC-coated insulated conductor with coiled copper shielding
- ultra-resistant thermoplastic-coated sheath

WATTAGE

- 50 W/ft² at 240 V and 347 V (3 in. spacing)
- 37.5 W/ft² at 208 V (3 in. spacing)

CONTROL

- snow melting system control (optional)

INSTALLATION

- never cut the cable
- suitable for residential or commercial outdoor use only
- can be installed under asphalt, concrete and pavers

WARRANTY

- ten years

IDEAL FOR:

driveway, stairs, sidewalk, walkway, pavers, terrace, public thoroughfare, garage entryway, parking lot, loading bay



Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_SSC_SSCM_EN_280420

MAT

TECHNICAL SPECIFICATIONS

PRODUCT	VOLTAGE	DIMENSIONS (FT)		AREA	POWER	AMPERAGE	POWER DENSITY	PRICE
CODE	VOLTS	WIDTH	LENGTH	FT ²	WATTS	AMPS	W/FT ²	
240/208 VOLTS								
SSCM2W0500L2S010	240/208	2	5	10	500/375	2.1/1.8	50/37.5	168.00
SSCM2W1000L2S020	240/208	2	10	20	1000/750	4.2/3.6	50/37.5	281.00
SSCM2W1500L2S030	240/208	2	15	30	1500/1125	6.3/5.4	50/37.5	388.00
SSCM2W2000L2S040	240/208	2	20	40	2000/1500	8.3/7.2	50/37.5	501.00
SSCM2W2500L2S050	240/208	2	25	50	2500/1875	10.4/9.0	50/37.5	609.00
SSCM2W3000L2S060	240/208	2	30	60	3000/2250	12.5/10.8	50/37.5	721.00
SSCM2W3500L2S070	240/208	2	35	70	3500/2625	14.6/12.6	50/37.5	854.00
SSCM2W4000L2S080	240/208	2	40	80	4000/3000	16.7/14.4	50/37.5	942.00
SSCM2W4500L2S090	240/208	2	45	90	4500/3375	18.8/16.2	50/37.5	1099.00
SSCM2W5000L2S100	240/208	2	50	100	5000/3750	20.8/18.0	50/37.5	1166.00
SSCM2W6000L2S120	240/208	2	60	120	6000/4500	25.0/21.6	50/37.5	1386.00
SSCM2W1500L3S030	240/208	3	10	30	1500/1125	6.3/5.4	50/37.5	378.00
SSCM2W3000L3S060	240/208	3	20	60	3000/2250	12.5/10.8	50/37.5	706.00
SSCM2W3750L3S075	240/208	3	25	75	3750/2813	15.6/13.5	50/37.5	916.00
SSCM2W4500L3S090	240/208	3	30	90	4500/3375	18.8/16.2	50/37.5	1029.00
SSCM2W6000L3S120	240/208	3	40	120	6000/4500	25.0/21.6	50/37.5	1350.00
347 VOLTS								
SSCM3W4000L2S080	347	2	40	80	4000	11.5	50	942.00
SSCM3W5000L2S100	347	2	50	100	5000	14.4	50	1166.00
SSCM3W6000L2S120	347	2	60	120	6000	17.3	50	1386.00
SSCM3W3000L3S060	347	3	20	60	3000	8.6	50	706.00
SSCM3W4500L3S090	347	3	30	90	4500	13.0	50	1029.00
SSCM3W6000L3S120	347	3	40	120	6000	17.3	50	1350.00

CABLE

(3 in. spacing)

TECHNICAL SPECIFICATIONS

PRODUCT	VOLTAGE	DIMENSIONS (FT)		AREA	POWER	AMPERAGE	POWER DENSITY	PRICE
CODE	VOLTS	LENGTH		FT ²	WATTS	AMPS	W/FT ²	
240/208 VOLTS								
SSC2W0450S009	240/208	37		9	450/338	1.9/1.6	50/37.5	151.00
SSC2W1000S020	240/208	84		20	1000/750	4.2/3.6	50/37.5	252.00
SSC2W1400S028	240/208	118		28	1400/1050	5.8/5.0	50/37.5	348.00
SSC2W2000S040	240/208	168		40	2000/1500	8.3/7.2	50/37.5	449.00
SSC2W2500S050	240/208	209		50	2500/1875	10.4/9.0	50/37.5	546.00
SSC2W3000S060	240/208	251		60	3000/2250	12.5/10.8	50/37.5	646.00
SSC2W4000S080	240/208	335		80	4000/3000	16.7/14.4	50/37.5	845.00
SSC2W4500S090	240/208	375		90	4500/3375	18.8/16.2	50/37.5	1037.00
SSC2W5000S100	240/208	420		100	5000/3750	20.8/18.0	50/37.5	1046.00
SSC2W6000S120	240/208	500		120	6000/4500	25.0/21.6	50/37.5	1242.00