

STZB402 | KI™ ZIGBEE

ELECTRONIC THERMOSTAT FOR SMART HOME

4000 W



CONNECTED COMFORT

The Ki Zigbee thermostat can easily be integrated into your home's Zigbee network, so you can adjust the temperature setpoint of rooms in your home from a distance.



INTEGRATES EASILY WITH A SMART HOME HUB



CONTROL WITH A MOBILE APPLICATION
DEPENDING ON HUB



ELECTRICITY SAVINGS
ENERGY SAVINGS OF 10-15%
DEPENDING ON USE*

COMPATIBILITY

- Maestro controller-thermostat or Zigbee hub required

COLOR

- white

FINISH

- molded plastic

WATTAGE AND VOLTAGE

- 150 W to 2000 W @ 120 V
- 300 W to 4000 W @ 240 V

CONTROL

- three functions available: comfort, economy and off
- two- or four-wire connection
- simple programming
- outdoor temperature display†
- compatible with forced-air units
- frost-free warning
- display in Celsius or Fahrenheit
- backlit screen with adjustable intensity
- activate several other functions

ACCURACY

- accurate ambient temperature control of ± 1 °F
- CSA C828-13
- temperature sensing with thermistor

TEMPERATURE RANGE

- 41 to 86 °F

WARRANTY

- three years

* independent study

† depending on the central controller and its application

COMPATIBLE WITH



FOR HOME AUTOMATED SYSTEM COMPATIBILITIES AND INSTRUCTIONS ON CONNECTING TO YOUR KI THERMOSTAT, VISIT WWW.STELPRO.COM.

TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	PACKAGING
	CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	
STZB402WB+	150/300	2000/4000	120/240	16.7	50/60	BOX

Dimensions: 4 7/8 in. wide, 4 7/8 in. high and 1 3/8 in. deep

STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-color products. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_STZB402_US_010520