

SMC402AD | MAESTRO™

SMART CONTROLLER • THERMOSTAT





4000 W

MAESTRO™



ORCHESTRATING COMFORT

Maestro is the first smart thermostat compatible with all your electric heating devices, such as baseboards, convectors and fan heaters. As the heart of your heating ecosystem, the Maestro controller•thermostat not only offers multiple features through its mobile app, it also gives you peace of mind, optimizes your comfort and saves energy. The Maestro solution is intuitive, accessible and smart. Maestro ensures you always stay comfortable by adjusting to your lifestyle. Turning your house into a smart home has never been easier!

- 
SIMPLE AND INTUITIVE MOBILE APP
 CONTROL AT YOUR FINGERTIPS WITH YOUR SMARTPHONE OR MOBILE DEVICE
- 
CREATE PERSONALIZED ACTIVITIES
 THAT INTEGRATE EASILY INTO THE SMART HOME
- 
GEOFENCING FEATURE
 FOR OPTIMAL ENERGY EFFICIENCY
- 
ELECTRICITY SAVINGS
 ENERGY SAVINGS UP TO 25% DEPENDING ON USE*

COMPATIBILITY

- Wi-Fi b/g/n
- Zigbee 3.0

COLOUR

- black

FINISH

- molded plastic

WATTAGE AND VOLTAGE

- 300 W to 4000 W @ 240 V
- 260 W to 3400 W @ 208 V
- 150 W to 2000 W @ 120 V

CONTROL

- access to the Maestro environment and application
- colour touch screen
- graphical colour-code to ensure smart energy consumption
- optimized early start-up based on outdoor temperature

- radical temperature decrease detection (open-window feature)
- weather conditions display
- energy consumption assessment
- home group monitoring and control

ACCURACY

- accurate ambient temperature control of ± 0.5 °C (1 °F)
- CSA C828-13
- temperature sensing with thermistor

TEMPERATURE RANGE

- 5 to 30 °C (from 41 to 86 °F)

WARRANTY

- three years
- * study conducted by an independent university team

ACCESSORIES

PRODUCT	DESCRIPTION	PRICE
SMAMPLIZB	Zigbee signal amplifier	96.00
SMREPETZB	Zigbee signal repeater	65.00

TO DOWNLOAD THE APPLICATION:



TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	COLOUR	PACKAGING	UNIT PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ			
SMC402AD	150/260/300	2000/3400/4000	120/208/240	16.7	60	BLACK	BOX	215.00

Dimensions: 5 3/8 in. (137 mm) wide, 5 3/8 in. (137 mm) high and 1 1/4 in. (32 mm) deep

°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-colour products. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_SMC402AD_EN_280420