

# ASMC402AD | MAESTRO™

SMART CONTROLLER • THERMOSTAT





4000 W

MAESTRO™



## ORCHESTRATING COMFORT

Maestro is the first smart thermostat compatible with all your electric heating devices, such as baseboards, convectors and fan heaters. As the heart of your heating ecosystem, the Maestro controller•thermostat not only offers multiple features through its mobile app, it also gives you peace of mind, optimizes your comfort and saves energy. The Maestro solution is intuitive, accessible and smart. Maestro ensures you always stay comfortable by adjusting to your lifestyle. Turning your house into a smart home has never been easier!

- 
**SIMPLE AND INTUITIVE MOBILE APP**  
 CONTROL AT YOUR FINGERTIPS WITH YOUR SMARTPHONE OR MOBILE DEVICE
- 
**CREATE PERSONALIZED ACTIVITIES**  
 THAT INTEGRATE EASILY INTO THE SMART HOME
- 
**GEOFENCING FEATURE**  
 FOR OPTIMAL ENERGY EFFICIENCY
- 
**ELECTRICITY SAVINGS**  
 ENERGY SAVINGS UP TO 25% DEPENDING ON USE\*

### COMPATIBILITY

- Wi-Fi b/g/n
- Zigbee 3.0

### COLOR

- black

### FINISH

- molded plastic

### WATTAGE AND VOLTAGE

- 300 W to 4000 W @ 240 V
- 260 W to 3400 W @ 208 V
- 150 W to 2000 W @ 120 V

### CONTROL

- access to the Maestro environment and application
- color touch screen
- graphical color-code to ensure smart energy consumption
- optimized early start-up based on outdoor temperature

- radical temperature decrease detection (open-window feature)
- weather conditions display
- energy consumption assessment
- home group monitoring and control

### ACCURACY

- accurate ambient temperature control of  $\pm 1$  °F
- CSA C828-13
- temperature sensing with thermistor

### TEMPERATURE RANGE

- 41 to 86 °F

### WARRANTY

- three years

\* study conducted by an independent university team

## ACCESSORIES

PRODUCT	DESCRIPTION
SMAMPLIZB	Zigbee signal amplifier
SMREPETZB	Zigbee signal repeater

### TO DOWNLOAD THE APPLICATION:



## TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	COLOR	PACKAGING
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ		
ASMC402AD	150/260/300	2000/3400/4000	120/208/240	16.7	60	BLACK	BOX

Dimensions: 5 3/8 in. wide, 5 3/8 in. high and 1 1/4 in. deep

°STELPRO

Stelpro reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-color products. For all the latest models and prices, please refer to our website at [www.stelpro.com](http://www.stelpro.com).



FC\_SMC402AD\_JUS\_280420