

ASOH – SONOMA™ HORIZON

SONOMA™ HORIZON

WALL FAN HEATER



THE CLASSIC FAN-HEATER OPTION

The Sonoma Horizon fan heater sets the bar high for optimal comfort. This quiet but fast heating solution is perfect for any room. Its resistant facade makes it a safe and sustainable choice. Easy to install, the Sonoma Horizon fan heater gives your room a classic touch.

■ DESIGNED WITH THE USER EXPERIENCE IN MIND

CONTROLS LOCATED AT THE TOP OF THE UNIT

■ CAN BE INSTALLED HIGH UP OUT OF THE REACH OF CHILDREN AND PETS

■ COMPACT FIT ANYWHERE, PERFECT FOR SMALL SPACES

■ OPTIMAL SAFETY INTEGRATED THERMAL CUTOFF RESISTANT FACADE

■ FAST COMFORT RAPID TEMPERATURE RISE

■ QUIET FAN

COLOR

- white

FINISH

- epoxy-polyester powdercoat

MANUFACTURING

- 22-gauge steel cabinet and 20-gauge steel grille
- thermal protections with manual reset
- additional one-time thermal fuse

ELEMENT

- nichrome element produces instant heat

CONTROL

- built-in thermostat (optional)
- wall thermostat (not included) – the use of an electronic thermostat is strongly recommended

INSTALLATION

- recessed only
- bottom of the wall: 6 in. min. from floor
- top to the wall: 6 in. min. from ceiling

WARRANTY

- five years

IDEAL FOR:

hallway, lobby, living room, kitchen, bedroom, office

°STELPRO

Stelpro reserves the right to modify at any time the description, manufacturing, or price of its products. Additionally, Stelpro may apply restocking fees or refuse a refund based on one or more of the following criteria: optional color, custom product, assembly with low-demand options. For the latest product information and prices regarding the products, please visit the website www.stelpro.com.



TECHNICAL SPECIFICATIONS

WITHOUT CONTROL	BUILT-IN THERMOSTAT	VOLTAGE	POWER*		FLOW	HEAT RISE	WEIGHT
CODE	CODE	VOLTS	WATTS	BTU/H	CFM	°F	LB
ASOH1001WCW	ASOH1001T2W	120	1000 or 500	3413 or 1706	33	96	6.2
ASOH1008WCW	ASOH1008T2W	208	1000 or 500	3413 or 1706	33	96	6.2
ASOH1002WCW	ASOH1002T2W	240/208	1000/750 or 500/375	3413/2560 or 1706/1280	33	96	6.2
ASOH1501WCW	ASOH1501T2W	120	1500 or 750	5119 or 2560	44	108	6.2
ASOH1502WCW	ASOH1502T2W	240/208	1500/1125 or 750/560	5119/3839 or 2560/1911	44	108	6.2
ASOH2008WCW	ASOH2008T2W	208	2000 or 1000	6825 or 3413	44	144	6.2
ASOH2002WCW	ASOH2002T2W	240/208	2000/1500 or 1000/750	6825/5119 or 3413/2560	44	144	6.2

Add WBB for unit without back box (available for U.S. market only).

*Choice of power at installation

ACCESSORY

PRODUCT	DESCRIPTION
ASOBB6	back box (6)

TECHNICAL DRAWINGS

