



Made in
Canada



25-year
warranty



True Comfort is flexible, reliable and versatile

The True Comfort system is installed with cable spacers (included in the box) or an uncoupling membrane. The cable is suitable for small and large rooms as well as irregularly shaped rooms where the cable must be laid around obstacles. It is very easy to install after precisely calculating the area to be heated.

- **Easy to install**
- **Flexible and robust cable with minimal shape memory**
- **Adapts to rooms of all shapes and sizes**
- **Maintenance free**
- **Energy savings**
A heated mass retains heat more easily than air
- **Can be installed indoors in dry or wet environments**
- **Complete set, including:**
Heating cable, cable spacers, hot glue sticks, and installation guide

Manufacturing

- Heating elements covered with fluoropolymer insulation for greater reliability
- Paired and twisted dual conductor design to eliminate electromagnetic fields
- Conductors shielded with a copper braid to ensure safety and robustness
- Flexible PVC sheath with constant diameter for easy installation

Available voltages

- 120 V and 240 V

Powers

- **Cable spacers**
 - Alternated 2-3-2 in.: 14.4 W/ft²
 - 3 in.: 12 W/ft²
 - Alternated 3-4-3 in.: 10.3 W/ft²
 - 4 in.: 9 W/ft²
- **Uncoupling membrane**
 - 2 studs (2-1/2 in.): 14.4 W/ft²
 - Alternated 2-3-2 studs (2-1/2 - 3-3/4 in.): 11.5 W/ft²
 - 3 studs (3-3/4 in.): 9.6 W/ft²

Control

- Electronic thermostat for floor heating (sold separately)

Installation

- Installs in a few easy steps with an uncoupling membrane or the included patented cable spacers
- Compatible with all subfloors that accept thinset mortar or self-leveling underlayment
- Compatible with most floor coverings*
- Can be installed in a wet environment, such as a European style shower floor

Ideal for

- Bathroom, kitchen, living room, basement, bedroom, hall

Warranty

- Twenty-five years

* Validate installation details with the floor manufacturer

COVERAGE

PRODUCT NO	MSRP (CA \$)	CABLE COVERAGE WITH CABLE SPACERS (ft ²)				CABLE COVERAGE WITH UNCOUPLING MEMBRANE (ft ²)					
		2-3-2 IN ALTERNATED 14.4 W/ft ²	3 IN 12 W/ft ²	3-4-3 IN ALTERNATED 10.3 W/ft ²	4 IN 9 W/ft ²	STELPRO			OTHER BRAND		
						2 STUDS 14.4 W/ft ²	2-3-2 ALTERNATED STUD 11.5 W/ft ²	3 STUDS 9.6 W/ft ²	2 STUDS 14.9 W/ft ²	2-3-2 ALTERNATED STUD 12 W/ft ²	3 STUDS 10 W/ft ²
120 V - 3 W											
CGS120K0035K01*	491.00	8	10	11	13	8	10	12	8	10	12
CGS120K0061	322.00	14	17	19	22	14	17	21	13	17	20
CGS120K0098	357.00	21	26	30	35	22	27	32	21	26	31
CGS120K0122	375.00	26	33	38	43	27	34	40	26	33	39
CGS120K0194	478.00	41	51	59	67	43	53	63	40	51	61
CGS120K0230	532.00	48	60	70	80	50	62	75	48	60	72
CGS120K0304	578.00	64	79	92	105	66	82	98	63	79	95
240 V - 3 W											
CGS240K0069	338.00	15	19	22	25	16	20	23	15	19	23
CGS240K0147	411.00	31	39	45	51	33	40	48	31	39	47
CGS240K0173	451.00	37	46	53	60	38	47	57	36	46	55
CGS240K0220	520.00	46	58	67	76	48	60	72	46	58	69
CGS240K0244	555.00	51	64	74	85	53	66	79	51	64	77
CGS240K0283	575.00	59	74	86	98	62	77	92	59	74	89
CGS240K0351	641.00	73	91	106	121	76	95	113	72	91	110
CGS240K0459	812.00	95	119	138	157	99	123	148	94	119	143
CGS240K0528	851.00	109	136	158	180	114	141	169	108	136	164
CGS240K0608	950.00	125	156	182	207	130	163	195	124	156	188
CGS240K0695	1031.00	143	178	207	237	149	185	222	142	178	215
CGS240K0782	1143.00	161	200	233	266	167	209	250	159	200	241

*Includes a non-programmable thermostat.

TECHNICAL SPECIFICATIONS

PRODUCT NO	POWER (W)	CURRENT (A)	LENGTH (ft)
120 V - 3 W			
CGS120K0035K01*	104	0.9	35
CGS120K0061	183	1.6	61
CGS120K0098	293	2.5	98
CGS120K0122	366	3.1	122
CGS120K0194	580	4.9	194
CGS120K0230	689	5.8	230
CGS120K0304	958	8.0	304

TECHNICAL SPECIFICATIONS

PRODUCT NO	POWER (W)	CURRENT (A)	LENGTH (ft)
240 V - 3 W			
CGS240K0069	207	0.9	69
CGS240K0147	440	1.9	147
CGS240K0173	518	2.2	173
CGS240K0220	660	2.8	220
CGS240K0244	733	3.1	244
CGS240K0283	850	3.6	283
CGS240K0351	1055	4.4	351
CGS240K0459	1378	5.8	459
CGS240K0528	1582	6.6	528
CGS240K0608	1917	8.0	608
CGS240K0695	2032	8.5	695
CGS240K0782	2219	9.3	782

ACCESSORIES

PRODUCT NO	MSRP (CA \$)	DESCRIPTION
STSCC	31.00	Thermal floor sensor compatible with the PS120/240NP & PS120/240WF thermostats
PS120/240NP	209.00	Non programmable electronic thermostat 120/240 V with GFCI
PS120/240WF	252.00	Wi-Fi programmable electronic thermostat - 120/240 V with GFCI
FSK-03	43.00	STELPRO - Repair kit (for 1 splice) - Twin conductor surface cable (GS, HGS, CGS, CPS, TS)
HGSGG	25.00	STELPRO - Gauges for heating cable (pack of 20), includes glue stick
HGSMD054	211.00	STELPRO - Uncoupling membrane (roll of 54 ft ²)
HGSMD162	543.00	STELPRO - Uncoupling membrane (roll of 162 ft ²)