## ASAT402ZB | ALLIA™

### ZIGBEE THERMOSTAT FOR CONNECTED HOME















### **CONNECTED COMFORT**

The Allia thermostat leverages the Zigbee network so that you can set up your ecosystem to control room temperatures remotely. Entirely designed and manufactured in Canada, the Allia thermostat was developed specifically for the smart home. Depending on the hub you choose, you'll be able to adapt it to your daily routines and increase your comfort. The Allia is compatible with the most popular Zigbee hubs including the 4<sup>th</sup> generation Alexa Echo.

#### CONTROL AT THE TOUCH OF YOUR FINGERTIPS

BY CONNECTING THE THERMOSTAT TO A ZIGBEE COMPATIBLE HUB

# ■ UNPARALLELED ACCURACY FOR COMFORT WITHOUT TEMPERATURE FLUCTUATIONS

- SUITABLE FOR ALL ELECTRIC HEATERS
   BASEBOARDS, CONVECTORS
   AND FAN HEATERS
- ELECTRICITY SAVINGS ENERGY SAVINGS UP TO 20% DEPENDING ON USE\*

#### **COMPATIBILITY**

Zigbee hub

#### **COMMUNICATION ANTENNA**

· Zigbee 3.0

#### **COLOR**

· white

#### FINISH

molded plastic

#### WATTAGE AND VOLTAGE

- 150 W to 2000 W @ 120 V
- 260 W to 3400 W @ 208 V
- 300 W to 4000 W @ 240 V

#### **CONTROL**

- display lock
- sleep mode 2 intensity levels
- open window feature freeze protection (41°F) if a drastic temperature drop is detected
- lobby mode for fan heaters maintains the setpoint if a rapid drop in temperature is detected

#### **ACCURACY**

- accurately controls the ambient temperature to ±1°F
- CSA C828-19
- · thermistor temperature reading

#### **TEMPERATURE RANGE**

• 41 to 86 °F

#### WARRANTY

- three years
- \* study carried out by an independent university team

#### **COMPATIBLE WITH**





o amazon alexa

4<sup>th</sup> GENERATION ECHO

To find out which home automation systems are compatible with your Allia thermostat, visit https://www.stelpro.com/en/products/allia-smart-home-thermostat-asat402zb/

# TECHNICAL SPECIFICATIONS T WATTS VOLTAGE AMPERAGE FREG

PRODUCT	WAITS		VOLIAGE	AWIPERAGE	PREQUENCT
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ
ASAT402ZB	150 260 300	2000 3400 4000	120 208 240	16.7	60

Dimensions: 5 3/8 in. wide, 5 3/8 in. high and 1 1/4 in. deep





