

SCPT

CONSTANT WATTAGE PIPE FREEZE PROTECTION HEATING CABLE



SAY GOODBYE TO FROZEN PIPES

This preassembled heating cable is designed to prevent pipes from freezing and avoid water damage. The cable is easy to install thanks to its 120 V plug, and the integrated thermostat triggers heat only when necessary. The cable is installed on pipes under insulation and protects against freezing down to -40 °F. Ideal for metal or plastic pipes up to 1.5 in. in diameter.*

- **PREVENTS PIPE BREAKAGE AND WATER DAMAGE**
- **IDEAL FOR PLASTIC OR METAL PIPES**
- **LIGHTED PLUG POWER INDICATOR**
- **INTEGRATED THERMOSTAT THAT TRIGGERS AT 37 °F TO PREVENT FREEZING**

MANUFACTURING

- tough XLPE inner insulation
- AL foil and continuous ground braid
- weather resistant PVC (high-low temperature) out jacket
- twin conductor
- bending radius of 1 inch
- 2 ft cold lead with plug

WATTAGE

- 7 W/ft

CONTROL

- built-in thermostat

INSTALLATION

- install at a temperature above 14 °F

WARRANTY

- two years

*The cable must never cross over itself. Plastic pipes must always be filled with water.



QUICK AND EASY PLUG-IN INTO 120 V OUTLET

IDEAL FOR:

pipes at risk of freezing

°STELPRO

Stelpro reserves the right to modify at any time the description, manufacturing, or price of its products. Additionally, Stelpro may apply restocking fees or refuse a refund based on one or more of the following criteria: optional color, custom product, assembly with low-demand options. For the latest product information and prices regarding the products, please visit the website www.stelpro.com.



FC_SCPT_US_060824

TECHNICAL SPECIFICATIONS

| PRODUCT | LENGTH | POWER | AMPERAGE |
|-----------------|--------|-------|----------|
| CODE | FT | WATTS | AMPS |
| 120 VOLTS | | | |
| SCPT1W0021L0003 | 3 | 21 | 0.2 |
| SCPT1W0042L0006 | 6 | 42 | 0.4 |
| SCPT1W0063L0009 | 9 | 63 | 0.5 |
| SCPT1W0084L0012 | 12 | 84 | 0.7 |
| SCPT1W0105L0015 | 15 | 105 | 0.9 |
| SCPT1W0126L0018 | 18 | 126 | 1.1 |
| SCPT1W0168L0024 | 24 | 168 | 1.4 |
| SCPT1W0210L0030 | 30 | 210 | 1.8 |
| SCPT1W0280L0040 | 40 | 280 | 2.3 |
| SCPT1W0420L0060 | 60 | 420 | 3.5 |

