

ASHC CONVECTOR



EFFICIENT HEATING

Our ASHC convector has pleasing rounded sides and beautiful modern lines. It is available with or without an ultra-accurate built-in electronic thermostat, so you can choose the level of control you want. This attractive unit is available in two colors and many voltages making it suitable for both commercial and residential applications. A real gem!

- **EXCELLENT VALUE**
- **TOTALLY QUIET**
- **BUILT-IN ELECTRONIC THERMOSTAT (OPTIONAL) WITH A BACKLIT SCREEN**
- **ADAPTS TO MULTIPLE MARKETS**
AVAILABLE IN: 120 V, 208 V, 240 V, 277 V AND 480 V

COLORS

- **standard:** white
- **Orora (optional):** refer to www.stelpro.com/en-US/Orora

FINISH

- epoxy-polyester powdercoat

MANUFACTURING

- 22-gauge steel cabinet and 20-gauge steel front
- the cabinet height improves the chimney effect
- bottom air intake and front air discharge
- 6 ft (2 m) 16 gage molded cable with 3-prong grounded, 120 V plug (ASHC1501P model)

CONTROL

- electronic thermostat required: built-in electronic thermostat with LCD screen (optional) or electronic wall thermostat (not included)

INSTALLATION

- surface mounted only
- wall mounted at least 4 in. from the floor
- concealed mounting bracket (included)
- back entry plate with cable clamps (included)

WARRANTY

- five years, *three years on electronic components

ELEMENTS

- two stainless steel tubular sheathed elements insulated with nylon sleeves to reduce expansion and contraction noises



BUILT-IN ELECTRONIC THERMOSTAT AVAILABLE FOR THE 120 V TO 240 V MODELS



ALSO AVAILABLE
QUICK AND EASY PLUG-IN INTO 120 V OUTLET

IDEAL FOR:

kitchen, living room, bedroom, office, basement, commercial space

°STELPRO

Stelpro reserves the right to modify at any time the description, manufacturing, or price of its products. Additionally, Stelpro may apply restocking fees or refuse a refund based on one or more of the following criteria: optional color, custom product, assembly with low-demand options. For the latest product information and prices regarding the products, please visit the website www.stelpro.com.



TECHNICAL SPECIFICATIONS

BUILT-IN THERMOSTAT CODE	WITHOUT THERMOSTAT CODE	POWER		VOLTAGE	HEIGHT	LENGTH	WEIGHT
		WATTS	BTU/H	VOLTS	IN.	IN.	LB
ASHC0501W	ASHC0501WCW	500	1706	120	17 9/16	17 5/16	11.2
ASHC0508W	ASHC0508WCW	500	1706	208	17 9/16	17 5/16	11.2
ASHC0502W	ASHC0502WCW	500/375	1706	240/208	17 9/16	17 5/16	11.2
---	ASHC0507WCW	500	1706	277	17 9/16	17 5/16	11.2
ASHC1001W	ASHC1001WCW	1000	3413	120	17 9/16	22 7/8	13.3
ASHC1008W	ASHC1008WCW	1000	3413	208	17 9/16	22 7/8	13.3
ASHC1002W	ASHC1002WCW	1000/750	3413	240/208	17 9/16	22 7/8	13.3
---	ASHC1007WCW	1000	3413	277	17 9/16	22 7/8	13.3
---	ASHC1005WCW	1000	3413	480	17 9/16	22 7/8	13.3
ASHC1501W	ASHC1501WCW	1500	5119	120	17 9/16	28 5/8	15.7
ASHC1508W	ASHC1508WCW	1500	5119	208	17 9/16	28 5/8	15.7
ASHC1502W	ASHC1502WCW	1500/1125	5119	240/208	17 9/16	28 5/8	15.7
---	ASHC1507WCW	1500	5119	277	17 9/16	28 5/8	15.7
---	ASHC1505WCW	1500	5119	480	17 9/16	28 5/8	15.7
ASHC2008W	ASHC2008WCW	2000	6825	208	17 9/16	35	18.9
ASHC2002W	ASHC2002WCW	2000/1500	6825	240/208	17 9/16	35	18.9
---	ASHC2007WCW	2000	6825	277	17 9/16	35	18.9
---	ASHC2005WCW	2000	6825	480	17 9/16	35	18.9
MODEL WITH 120 V PLUG (RESIDENTIAL OUTLET)							
ASHC1501PW*	---	1500	5119	120	17 9/16	28 5/8	15.7

Consult the optional colors chart or contact your Stelpro representative for all other colors.
 Mechanical wall thermostats are not compatible with the without thermostat model (WC) – electronic thermostat is required.
 * Available in white only
 --- not available

ACCESSORIES

PRODUCT	DESCRIPTION
SHCRE153*	built-in electronic low voltage relay [15 A @ 120 V-347 V]
SHCRE156*	built-in electronic low voltage relay [6 A @ 600 V]
SHCRE153T*	built-in electronic low voltage relay c/w transformer 24 V [15 A @ 208 V-347 V]

Electronic relays can receive a PWM (pulsed width modulation) or digital (on/off) signal.
 * Factory installed

TECHNICAL DRAWINGS

